

Slick-Line Unit Information Pack

March 2015

Specification-Description

The equipment comprises the following items (in summary):

- **Skid Mounted Slick-Line Unit, Diesel Generator**
- Type: Skid unit, mounted on UK trailer, diesel engine for driving hydraulics, with on-board diesel generator for power supply. Unit was built in 1997, then completely rebuilt in 2010 before being supplied to UK.
-
- Specs: Split drum unit, with 20,000 feet, 0.125 inch, 316 Stainless Steel line (never used to date); 12,000 feet of 0.125 inch 316 line, (USED but in good condition). Closed loop hydraulics capable of working at depths to 15,000 ft.
-
- Measurement and Control: “Line-Wise” digital depth measurement that provides digital readout of depth, pressure, line weight and line speed. All data is presented on screen in real time, with a memory card back-up of readings taken every 1 second. Backup mechanical depth measurement (Halliburton head with Veeder Root) and mechanical weight indicator.
-
- Pressure Control: 5000 psi, 24 feet (8 feet segments) lubricator stand pipe and pack-off, with 5000 psi wire BOP, all connected with Bowen unions (non H2S service). 10,000 psi H2S service lubricator, pack-off and BOP, (32 feet total, 8 feet segments).
- 5000 psi Lubricator (BOP, 6 sections, lifting head)
- 10,000 psi BOP Lubricator (Frank Henry)
- Selection of wire-line tools, accessories and spares















